THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

1.	PRODUCT	AND	COMPANY	IDENTIFICATION	MSDS Number: 25839
					Version Date: 10/10/2002

Product Name: THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

Product Use: Octane booster

Synonyms: 5040912

Manufacturer

Pennzoil-Quaker State Company Outlaw Products

P.O. Box 2967

Houston, TX 772522967

USA

Phone Numbers

Medical Emergency: 1-800-546-6040

Transportation Emergency (USA): 1-800-535-5053

Transportation Emergency (International):

1-352-323-3500 (Call Collect)

MSDS Assistance: 1-800-546-6227 Fax On Demand: 1-800-546-6227 Technical Assistance: 1-800-458-4998 Customer Service: 1-800-468-8397

Fax Number: 713-217-3181

Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
PETROLEUM DISTILLATES	MIXTURE	95 - 99	Yes
FUEL ADDITIVE	TRADESECRET	1 - 5	Yes
MMT (MANGANESE TRICARBONYL METHYLCYCLOPENTADIENYL)	12108-13-3	< 1	No

Hazards:
Flammable/Combustible X Acute Toxin X Chronic Toxin X Carcinogen
Pressure Reactive Exposure Limit X Target Organ X Other

Other: No information available

3. HAZARDS IDENTIFICATION

Emergency and Hazards Overview

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

This product is HAZARDOUS according to OSHA 29 CFR 1910.1200.

NFPA Ratings: Health 1 Flammability 2 Reactivity 2

Primary Route of Exposure: Skin X Inhalation X Eye

Health Effect Information

Eye Contact: Avoid eye contact. This product is minimally irritating to the eyes upon direct contact.

Based on testing of similar products and/or components. This product has a low vapor pressure and is not expected to present a hazard to the eyes at ambient conditions. Exposure to high concentrations of vapors may be irritating to the eyes.

Skin Contact: Avoid skin contact. This product is minimally irritating to the skin upon direct contact. Based on testing of similar products and/or components. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. See Section 11 - Toxicological Information.

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

irritating to the respiratory tract. Severe intoxication may lead to drowsiness, dullness, numbness,

Inhalation: Avoid prolonged inhalation of mist or vapors. This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. Acute and chronic overexposures may be

and headache followed by dizziness, weakness, and nausea.

Ingestion: Do not ingest. Ingestion of large quantities may be harmful. Ingestion of small quantities is usually nonfatal unless aspiration occurs. Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting with a further risk of aspiration. Ingestion may cause gastrointestinal distress. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

Other: No information available

MSDS Number: 25839

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

Skin Contact: Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. Use a hand or skin lotion to prevent dryness.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. If victim exhibits signs of vapor intoxication remove to fresh air. If breathing has stopped or is irregular, administer artificial respiration and supply oxygen if it is available. If victim is unconscious, remove to fresh air and seek immediate medical attention.

Ingestion: Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. Seek immediate medical attention.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: 140 F, 60 C

Flash Point: No data available

Test Method: ASTM D 3828-81-Setaflash
Test Method: No information available

Flammable Limits in Air

Upper Percent: No data available Lower Percent: No data available

Autoignition Temperature: No data available Test Method: No information available

NFPA Classification: Class III-A combustible liquid

Extinguishing Media: Use dry chemical, foam, or carbon dioxide.

Page 2 of 8

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

Fire Fighting Measures

MSDS Number: 25839

Special Fire Fighting Procedures and Equipment: Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture.

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: None

Other: No information available

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Remove all sources of ignition. Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Provide adequate ventilation during clean-up.

Regulatory Notifications: Notify appropriate authorities of spill.

Containment and Clean up: Contain spill immediately. Do not allow spill to enter sewers or watercourses. Absorb with solvent absorbent material. Large spills may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106-Flammable and Combustible Liquids.

Storage: Do not transfer to unmarked containers. Store in a cool, well ventilated area in closed containers away from heat, sparks, open flame or oxidizing materials.

Empty Container Warnings

Drums: Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed. Empty containers retain product residue and can be dangerous. DO NOT PRESSURIZE, CUT WELD, BRAZE SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Plastic: Do not reuse this container. Empty container may retain product residues.

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

Component	CAS No.	Exposure Limit
MMT (MANGANESE TRICARBONYL	12108-13-3	OSHA - PEL: TWA 0.2 mg/m3 Skin (as
METHYLCYCLOPENTADIENYL)		Mn)
		ACGIH - TLV: TWA 0.2 mg/m3 Skin (as
		Mn)

Page 3 of 8

Page 4 of 8

MSDS Number: 25839

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

Personal Protective Equipment

- Eye/Face Protection: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.
- Skin Protection: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.
- Respiratory Protection: Respiratory protection is not required under conditions of normal use. If concentrations are greater than the limits in Sections 8 or 3, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.
- **Personal Hygiene:** Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

Engineering Controls / Work Practices

Ventilation: If vapor or mist is generated when the material is heated or handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure or flammable limits. See also Fire and Explosion Information in Section 5.

Other: As a precaution, all exposure to mists and vapors of petroleum products should be minimized. The OSHA permissible exposure limit (PEL) and ACGIH threshold limit value (TLV) for oil mist is 5 mg/m3. Chronic exposures below 5 mg/m3 are without significant health risks. The ACGIH short-term exposure limit (STEL) for oil mist is 10 mg/m3. The OSHA PEL for petroleum distillates is 2000 mg/m3. NIOSH recommendeds a 10-hour TWA of 100 mg/m3 for kerosene.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, brown Odor: Aromatic	Vapor Pressure: No data available
Physical state: Liquid	Vapor Density (air=1): No data available
pH: No data available	Percent Volatile by Volume: No data available
Boiling Point: No data available	Volatile Organic Content: No data available
Melting Point: No data available	Molecular Weight: No data available
Specific Gravity: 0.82	Average Carbon Number: No data available
Pour Point: No data available	Viscosity @ 100 F: No data available
I OHI I OHIO TTO GATE ATTRIBUTE	Viscosity @ 40 C: No data available
Solubility in Water: Negligible in water	
Octanol / Water Coefficient: Log Kow = N	lo data available

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: High heat and open flames.

Incompatible Materials to Avoid: May react with strong oxidizing agents.

Other: No information available

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

11. TOXICOLOGICAL INFORMATION

MSDS Number: 25839

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: LD50 (rabbit) > 2 gm/kg - MMT.

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: A 90 day chronic inhalation study of MMT indicated that 3 mg/cu.M of MMT

showed detectable effects in mice.

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Carcinogenicity: The International Agency for Research on Cancer (IARC) has concluded that light and

intermediate middle distillates are Group 3 substances, "not classifiable as to their carcinogenicity

to humans," based on inadequate human and inadequate animal evidence.

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: No information available

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded, may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility. Materials should be recycled if possible.

Other: No information available

Page 5 of 8

MSDS Number: 25839

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

14. TRA	ANSPORTATION INF	ORMATION
U.S. Depa	artment of Transporta	tion (DOT)
	ay / Rail (Bulk): NOT	
Highw	ay / Rail (Non-Bulk): (CONSUMER COMMODITY, ORM-D
	T description is provice the suitable for all ship	led to assist in the proper shipping classification of this product and oping descriptions.
		X IMDG Not Regulated: X ICAO Not Regulated:
Other: N	o information available	

15. Regulatory Information

<u>Regulatory Lists Searched</u>: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depletors, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

Inventories: 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA , 85 - China Inventory

Regulatory Search Results:

MMT (MANGANESE TRICARBONYL METHYLCYCLOPENTADIENYL): 15, 17, 41, 50, 61, 63, 64, 65, 66, 67, 68, 69, 80, 81, 82, 83, 84, 85

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313: Consumer products are not regulated under SARA, Title III, Section 313.

IARC: No information available

Page 7 of 8

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

SARA 311/312 Categories								
Acute:	X	Chronic:	X	Fire:	<u>X</u>	Pressure:	Reactive:	
Not Regulated:								

Canadian WHMIS Classification

- Class B Flammable and Combustible Material, Division 3, Combustible Liquid
- Class D Poisonous and infectious material, Division 2B, Toxic Material
- Class D Poisonous and infectious material, Division 2A, Very Toxic Material

European Union Classification

Hazard Symbols:

Dangerous for the environment / N / dead tree and fish in square Harmful / Xn / X in square.

Risk Phrases:

MSDS Number: 25839

R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Safety Phrases:

S2: Keep out of the reach of Children.

S23: Do not breathe gas/fumes/vapour/spray.

S24: Avoid contact with skin.

S61: Avoid release to the environment. Refer to special instructions/Safety data sheet.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

Front Label:

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

Read carefully other cautions on back.

Back Label:

DANGER: Contains petroleum middle distillates. Prolonged and repeated skin contact may cause drying of skin.

PRECAUTIONARY MEASURES: Keep away from heat and flames. Avoid breathing of mists and vapors. Use only in well ventilated areas. Avoid repeated and prolonged skin contact. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If inhaled, breathe fresh air. For skin or eye contact, wash thoroughly with water.

KEEP OUT OF REACH OF CHILDREN.

MSDS Revisions

Previous Version Date: Not applicable, this MSDS is the first version.

Previous Version Information

No information available

Other

THE OUTLAW TRUCK OFF ROAD POWER BOOSTER

No information available

Prepared By:

MSDS Number: 25839

Pennzoil-Quaker State Company Environmental, Safety, Health, & DOT Compliance P.O. Box 2967 Houston, TX 77252-2967 USA

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgement. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Pennzoil-Quaker State Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 8 of 8